

IN THE SPECIFICATION

On pages 1 and 2 beginning at paragraph 4, two line from the bottom and continuing on page 2 ending at line 10 of the script, the paragraph has been amended.

---

A1 As stated above, during the assembly of the cells and the recuperator core, the interface of the components are welded. The effectiveness of the welding process used to form the core is in many instances ~~depend~~ depended on the fitting relationship of the plurality of cells, the resulting configuration of the interface of the individual ones of the plurality of cells and the welding process itself. The results of these variables in some instances results in a leaking core, leakage between the donor passage and the recipient passage. Thus, it is necessary to inspect or check the reliability of the welded core against leaks prior to installing into the recuperator application. The inspection process adds cost to the finished core, which to insure reliability may be necessary, but the cost effectiveness of such an inspection process can reduce profitability. Inspection or checking must be done in a reliable and cost effective manner.

---

On page 2 beginning at paragraph 6 at line 14 and continuing to the bottom of the page, the paragraph has been amended.

---

A2 In one aspect of the invention, an apparatus for testing a leakage rate within a recuperator core is disclosed. The recuperator core has a plurality of components, such components being a plurality of cells being welded one to another. The apparatus has a platform defining a first end and a second end. A first surface of the platform extends between the first end and the second end. A first support portion is attached to the first surface and a second support portion is spaced spaced from the first support portion and each being attached to the first

112  
Cont  
surface. A pair of sealing mechanisms, at least one of the pair of sealing mechanisms being movable between an open or non testing position and a closed or testing position. In the closed or testing position a reservoir is formed. A pump being operatively connected to at least one of the pair of sealing mechanisms. A monitoring system being operatively connected to the platform, the pair of sealing mechanisms, the reservoir and the pump. And, a readout station being operatively connected to the monitoring system, the reservoir and the pump.

---

On pages 3 and 4 beginning at paragraph 10 at line 20 and continuing on page 2 ending at line 6 of the script, the paragraph has been amended.

---

113  
As best shown in Figure 1, a recuperator core 10 is formed from a plurality of cells 12. In this application, the recuperator core 10 has a circular shape and a cylindrical configuration, however, as an alternative any configuration of a recuperator core 10 can be tested. For example, the geometric shape or configuration of the recuperator could be a square, a trapezoidal or a rectangular, without changing the jest gist of the invention. The recuperator core 10 has a plurality of donor passages 14 and a plurality of recipient passages 16 defined therein. Each of the plurality of donor passages 14 has a donor inlet end 18 and a donor outlet end 20. Each of the plurality of recipient passages 16 has a recipient inlet end 22 and a recipient outlet end 24. The circular core 10 defines a central axis "A", an inside diameter "ID" and an outside diameter "OD". A plurality of welds 26 are used to complete the assembly of each of the plurality of cells 12. Additional welds 26, not shown, are used in forming and combining the plurality of cells 12 forming the circular recuperator core 10.

---

Further on page 4 beginning at paragraph 11 at line 7, the paragraph has been amended.

As best shown in Figure 2, a system, apparatus and/or assembly line 30 has an input end or station 32, a testing station 34, a control panel or operations station 36, a vacuum or pressure station 38 and an output end or station 40 operatively connected one with the other. The input end or station 32 has a tub or flat 50 positioned near the testing station 34. In this application, as best shown in Figure 3, the testing station 34 is positioned on a table or movable cart 52. The cart 52 has a top portion 54 on which is positioned a test stand 56. A bottom portion 58 of the cart 52, as best shown in Figure 3, has a set of rotatable wheels 60 attached thereto. The control panel 36 is operatively connected to the cart 52, such as by wires, and has a plurality of switches 62 operatively positioned therein. In this application, the control panel 36 is physically attached to the cart 52 and moves with the cart 52. A portion of the plurality of switches 62 are safety switches. The control panel 36 also has a monitoring system 64 operatively attached to the testing station 34 and the vacuum or pressure station 38. Another portion of the plurality of switches 62 are operatively connected to the test stand 56 of the testing station 34, the vacuum or pressure station 38 and the monitoring system 64, such as by wires. The vacuum or pressure station 38 has a source for pulling a vacuum or applying a pressure, a pump 66 and a plurality of lines 68 interconnected with the testing station 34. The monitoring system 64 has a plurality of sensors 70 operatively connected to the vacuum or pressure pump 66, the testing station 34 and the plurality of switches 62. The output end or station 40 has a pair of tubs or flats 72 positioned near the testing station 34. One of the pair of tubs or flats 72 defines an acceptable or operational position 74 for the core 10 to be placed thereon and the other of the pair of tubs or flats 72 defines a non acceptable or failed position 76 for the core 10 to be placed thereon.

On pages 5 and 6 paragraph 12 at line 3 has been amended.

The test stand 56 has a platform 80 defining a first end 82 and a second end 84. A first surface 86 of the platform 80 extends between the first end

82 and the second end 84. The first surface 86 is attached to the top portion 54 of the cart 32. A second surface 88 of the platform 80 is spaced from the first surface 84 a preestablished distance and extends between the first end 82 and the second end 84. A first support portion 90 of the test stand ~~65~~ 56 has a first end 92 attached to the second surface 88 near the first end 82. A pair of brace members 94 are interposed the first support portion 90 and the first end 82. A second support portion 96 has a first end 98 attached to the second surface 88 near the second end 84. An other pair of brace members 100 are interposed the second support portion 96 and the second end 84. The first support portion 90 and the second support portion 96 are spaced apart a preestablished axial distance "D". In this application, a brace 98 extends between a second end 102 of the first support portion 90 and a second end 104 of the second support portion 96. The first support portion 90 has a sealing member 110 attached thereto which operatively communicates with the core 10. The first support portion 90 has a valve member 114 attached thereto. A first end 116 of a pressure member 118, such as a cylinder 120, is operatively attached to the second support portion 96. A rod end 121 of the pressure member 118 is attached to a plate 122. The plate 122 is moved along the axial distance "D" and has an infinite number of positions. A sealing member 124 is attached to the plate 122. A source of flow 126, such a hydraulic pump or air compressor activates the cylinder 120 within the distance "D". The sealing member 124 is movable between an open or non-testing position 127 and a closed or testing position 128. With the sealing member 110, the core 10 and the sealing member 124 in the closed or testing position, a reservoir 125 is formed therebetween. The valve member 114 and the source for pulling a vacuum or applying a pressure, the pump 66 are operatively connected to the reservoir 125. As an alternative, the sealing member 110 could be movable forming the open or non-testing position 127 and the closed or testing position 128.

---

And further on page 6 and concluding on page 7 beginning at paragraph 15, the first paragraph under the heading, Industrial Applicability, the paragraph has been amended.

---

AB In operation, as best shown in ~~Figure 3~~ Figures 2 and 3, one of the cores 10 is removed from the tub 50 at the input end or station 32. The core 10 is positioned on the platform 80 of the test stand 56. The guard member 130 is positioned about the "OD" of the core 10 and the threaded member 144 of the tightening member 138 is threadedly engaged with the threaded boss member 140 maintaining the guard member 130 about the "OD" of the core 10 in a fixed position.

---

And further on page 7, paragraph 17 beginning on line 14 has been amended.

---

AT The operator actuates the program by using the control panel 36 and the system or apparatus or assembly line 30 is directed through the testing operation. For example, the operator defines and inputs the plurality of testing parameters. The identify of the core 10, serial number, first time test, multiple test or used core 10 is identified. And, the program precedes through the steps of the procedure. The results of the test is recorded and stored for future use and in most situations is printed on a hard copy. In some tests, the results of the test are stamped or visually marked on the core 10 itself. The test substantially uses a flow from the vacuum or pressure station 38 which enters or exits through the lines 68. After the pressure or vacuum, within the reservoir 125, reaches a predetermined value, the monitoring system 64 defines the rate of leakage within the plurality of donor passage 14 and/or plurality of recipient passages 16 and records the rate of leakage for future use. The plurality of light and/or signals 152 indicate to the operator the results of the test.

---